



产品特性/Product Features

- IP6K9K
- 350A 85°C长时间载流能力
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1
- PWM
-
-
-

触点参数 / Contact parameters

		1a	
		0.5m at 350A	
		350A	
		2×10^5	
		450型	750型
		750VDC	750VDC
		2000A 320VDC 1	2000A 320VDC 1
		135kW	225kW
1		5×10^4 32VDC, =1ms, 350A	5×10^4 32VDC, =1ms, 350A
		50 64VDC, =1ms, 650A	50 64VDC, =1ms, 650A
		1×10^3 450VDC, 350A	500 750VDC, 350A
		200 450VDC, -350A	100 750VDC, -350A
		1 450VDC, 2000A	1 450VDC, 2000A
z		350A:	
		450A:10min	
		600A:1min	
		2000A:1s	
		1NO	
辅助 接点	Ue	30VDC/125VAC	
		2A DC /3A AC	
		9V0.1A	

1) 23°C, 0.6s:5.4s.

2) 85°C, 150mm², " "

ZHEJIANG HUANFANG

性能參數 / Performance parameters

	1000MΩ(1000VDC)
	3000VAC 1min
	3000VAC 1min
()	≤30ms
()	≤10ms
	196m/s ²
	490m/s ²
	10Hz~500Hz 49m/s ²
	5%~85%RH
	-40°C~85°C
	/
	400g

繞圈參數 / Coil parameters

VDC	VDC	VDC	W
9~24V	9	≥4.5	26W 3W
-40°C~85°C)			

外形圖、安裝孔尺寸 / Outline drawing, mounting hole size

/Unit mm

性能曲线图 Performance graph

1

M5螺钉 (内螺纹)	3N·m	4N·m	Ø5.0~Ø5.5	5mm	M5螺钉	3N·m ~ 4N·m
M8	10N·m	12N·m	Ø8.0~Ø8.5	5mm		

2

150m

3

5mm